

Section _____ Town _____ Range _____

March 1810

I commenced a Survey of Section 33, T. 6, R. 7
for L. E. Leade & J. C. Leade et al
w. c. Leade J. M. Anderson Johnson
Hill and Peter Hill consulting

A. J. Lind } sworn
Thomas Fry } C. B.
J. F. Parker Secy

Surveyor Greene County.

CORNER ESTABLISHED.	Monument.	Device.	WITNESS POINTS OR BEARING TREES.	Mark or Dia. in Inches.	COURSE.	Links Distant.	REMARKS.
NE 33	stone	+	water oak	22	S 35 E	58	found 7m. Parker corner and wit stump
W 1/4 33	stone		Hickory	24	S 65 1/2 E	28	
center 1/4	stone		Hickory	24	S 20 1/2 W	104 1/2	
			ash	12	S 38 W	82	
E 1/4 SW	stone		Burr oak	18	N 86 1/2 E	8 1/2	
			do	18	S 64 W	14	
W 1/4 SW	stone		Bl. walnut		North	163	
SE 33	stake		SW cr. of west abutment of concrete culvert				
					N 52 W	10	
SW 33	stake		Maple	48	N 78 3/4 W	37	
S 1/2	stone		Burr oak	15	S 85 3/4 E	192	

Var.

Course.	Point of Beginning.	Chains Distance.	Corrected Bearings.
west	SE	41.30 1/2	S 1/4
		82.09	SW
South	NE	41.22	E 1/4
		82.38 1/2	SE
North	SW	82.58	NW
South	N 1/4	41.50	center
		82.40	S 1/4
East	W 1/4	41.22	center
		82.78	E 1/4
West	E 1/4 SW	40.98	W 1/4 SW
West	NE	83.00	NW